



CAMELOT

HIGH SOLIDS - HIGH PERFORMANCE FLOOR FINISH

High solids and high performance floor seal and finish designed for use with any floor maintenance system. High solids formulation requires fewer coats for better performance. Durable, brilliant clear gloss. Long lasting mark resistance. Use on vinyl, linoleum and terrazzo floors. Ideal for use with frequent buffing and burnishing programs including propane machines. Ideal for use in high traffic areas where optimal appearance is important.

DIRECTIONS

Read the entire label and SDS for proper use, handling and storage before using this product. For best results, floors should be clean, old coatings removed and the floor neutralized.

1. Apply finish in full uniform coats.
2. Allow to dry before recoating.
3. For maximum performance, apply additional coats of finish until the desired level of appearance and protection is achieved.
4. Allow to dry thoroughly before reopening area for traffic.

Buffing: This finish can be spray buffed or high speed buffed. Follow directions of buffing compound.

Stripping: This finish can be removed using a CMI high quality stripping solution.

APPLICATIONS

- High solids - high performance
- Brilliant gloss and appearance
- Use with any buffing/burnishing and floor maintenance program
- Reduces maintenance costs
- Durable, mark resistant

FOR USE IN

- Building Service Contractors
- Retail
- Education
- Healthcare
- Hospitality & Lodging

CHEMICAL & PHYSICAL PROPERTIES

Appearance	Opaque White Liquid
Odor	Acrylic
pH	8.0 - 9.0
Solid Content	25%
Coverage	1,500-2,000 square feet per gallon
Slip Resistance	Greater than 0.5% coefficient of friction. Meets or exceeds ASTM D-2047.

PACKAGING

N165-G4	4x1 gallon/case
N165-P5	5 gallon pail



Chemical Maintenance, Inc.
1100A West Bloomington Road, Champaign, Illinois 61821
217-359-6262 • www.cmiclean.com
Refer to SDS for more information.